

HARDFLOOR SAVER INSTRUCTIONS

Q: What is Hard Floor Saver?

A: Hard Floor Saver is a tough 85um plastic film with a light adhesive coating.

Q: How long can I leave it down?

A: It may be left on up to a maximum of 60 days

Q: Can I put it on all types of flooring?

A: No, it should only be installed on Ceramic tiles, factory finished hard wood floors & other smooth finished surfaces. Under no circumstances should you install on site finished hard wood flooring.

Q: Can I install this in direct sunlight?

A: No, it is recommended that you avoid prolonged periods of sun exposure on this product.

Q: Oops, I accidentally installed it on the wrong surface. What do I use to clean it?

A: Citrus based cleaners are generally effective in removing the adhesive, but first make sure that any cleaner used complies with the surface manufacturer's instructions.

Instructions:

1. Peel off outer dust cover and retain.
2. Start by peeling back beginning of roll.
3. Position roll where needed and roll out film over area needed and cut using sharp knife. Repeat this until area completely covered.
4. Re-apply dust cover over remaining roll for later use.

NOTE THE FOLLOWING:

Surface must be free of moisture, grease and dust.

Apply to entire floor surface only. DO NOT APPLY in sections of rooms as the film will remove any dirt or dust that is there and it may look different to the uncovered surface.

Check the product weekly by peeling back to ensure it has not reacted to the surface.

*The manufacturer or supplier will not be held responsible for incorrect usage of this product.